



Product data
Floorify® Rigid Vinyl Planks & Tiles
 click

version:

1/10/2025

EN

Dimensions and basic data

		Chevron		
Width	ISO24342	305	mm	
Length	ISO24342	1293	mm	
Number of panels per pack	-	4	pc	
m ² per pack	-	1,58	m ²	
Weight per pack	ISO23997	19,9	kg	
Total thickness	ISO24346	6	mm	
Top Layer thickness	ISO24340	0,55	mm	
Core	-	Sound reducing, robust and waterproof Floorify® Rigid Core		
Finish	-	Protected with stain resistant Floorify® Quiet Sense Technology		
Locking method	-	Traditional glueless click under license of Välinge 5G		

Warranty

	Usage class	ISO10582	33
	CE	EN 14041	DoP FF001
	Warranty	Residential / Commercial	Residential: 25 years (Lifetime when installed on Floorify® Performance subfloor) Commercial: 5 years (10 years when installed on Floorify® Performance subfloor) For the Czech, Slovak and Hungarian markets: the warranty also applies to the Arbiton Secura Aquastop Smart 3in1 2.2 or 3 mm underlay. The lifetime or extended warranty also applies to the Arbiton Secura LVT CLICK SMART 1.5 mm 3in1 underlay.

Technical data

		Norm	Norm Requirements	Floorify® results
	Wear resistance	ISO24338 Procedure A	≥ 2000 cycles	≥ 4000 cycles - AC4
	Impact resistance	EN13329	≥ 1600 mm	In combination with Floorify underlays: > 1800mm - IC3
	Residual indentation	ISO24343-1	≤ 0,2 mm	OK in combination with Floorify underlays
	Stain resistance	EN438-2	Groups 1 and 2: grade 5; Group 3: grade 4	Groups 1, 2 and 3: grade 5
	UV resistance	ISO 105-B02:2014, Method 3	≥ 6	> 6
	Fire classification	EN 13501-1 ISO 9239-1	-	Bfl-s1
	Dimensional stability	EN ISO23999 Gur bij 80C	≤ 0,15 % Curling ≤ 2mm	≤ 0,10 %
	Locking strength	ISO24334	Long side: ≥ 1kN/m Short side: ≥ 1,5kN/m	Long side: > 5kN/m Short side: > 5kN/m
	Displacement of furniture feet	EN ISO16581	Foot 0,1mm / 32kg	No changes

	Castor chairs	EN ISO 4918	≥ 25000 cycles: No delamination, no disturbance	OK in combination with Floorify underlays
	Slip resistance	EN13893 EN 16165	-	DS R10
	Thermal resistance (floor + underlay)	EN12667	< 0,15R (m²K/W)	0,0264 R24 (m²K/W) (0,0153 floor + 0,0093 Performance underlay) 0,0693 R24 (m²K/W) (0,0153 floor + 0,0540 Comfort underlay)
	Floor heating	Appropriate for all standard heating systems IN cement flooring. It is suitable for heating foils, max. power consumption 80W/m²		
	Impact sound improvement	ISO 10140 / ISO717-2	ΔLw18dB	In combination with Floorify® Comfort underlay: ΔLw18dB
Dangerous Substances				
	Formaldehyde emission	EN14041 / EN717-1	-	E1
	TVOC 28 days	< 1000µg/m³	-	< 10µg/m³
	Emissions in the interior air	Decree n° 2011-321	-	A+
	REACH	-	-	Floorify® floors and accessories are fully REACH compliant
	Plasticizers	-	-	DOTP - virgin PVC - 100% orthophthalate free

Floorify NV reserves the right to make alterations to material and structures when this serves to improve the quality
Floorify NV, Kwadestraat 151, 8800 Rumbeke, BELGIUM - Email: hello@Floorify.com - T +32 (0)51 140 180